



Flextech Engineering Inc.
www.flextechseals.com

Product Description

Fiberglass gasket tape is ideal for applications at and below 1000 °F.



Fiberglass Gasket Tape

For applications to 1000 °F

"E" Fiberglass Composition

<u>Silicone Dioxide</u>	<u>52-56%</u>
<u>Calcium Oxide</u>	<u>16-25%</u>
<u>Aluminum Oxide</u>	<u>10-12%</u>
<u>Boron Oxide</u>	<u>8-12%</u>
<u>Magnesium Oxide</u>	<u>0-6%</u>
<u>Sodium Oxide</u>	<u>0-1%</u>
<u>Potassium Oxide</u>	<u>0-1%</u>

- Nonflamable
 - Will not stretch or shrink
 - High tensile strength
 - Chemically inert*
 - High Dielectric strength
 - Excellent flexibility retention to 1000 °F
 - Low Thermal conductivity
 - Meets U.S. Coast Guard requirements
- *except hydroplouric, phosphoric, HCl

Available Sizes

<u>Thickness</u>	<u>1/32", 1/16", 1/8" 1/4", 1/2"</u>
<u>Width</u>	<u>1/2", 1", 1 1/2", 2", 3", 4", 6"</u>
<u>Roll Size</u>	<u>100 Ft lengths</u>

Available Coatings:

Vermacite, Teflon, Silicone, Aluminum, Neoprene, and Viton.

Gasket tapes are available in drop warp style, and with adhesive backing